

What is claimed is:

sub 1) 1. A method for centrally managing a computer network, including of:

maintaining a central database of all NASes known to the computer network; and

5 broadcasting a message to a NAS list located at each POP in the computer network whenever said central database is changed, said message containing information regarding the change.

2. The method of claim 1, wherein all of said NASes known to the computer network  
10 are all NASes within the computer network which have been chosen as being valid.

3. The method of claim 1, wherein said maintaining is performed by a Network  
Control Console.

15 4. The method of claim 3, wherein said Network Control Console is a graphical interface.

5. The method of claim 1, wherein said maintaining includes adding NASes, deleting  
NASes, and modifying the entries of NASes in said central database as the need arises.

20 6. The method of claim 1, wherein said broadcasting is performed automatically by a broker whenever a change to said central database is made.

7. The method of claim 1, wherein said broadcasting includes publishing a broker event via a broker.

8. A method for locally processing an access request at a Point-of-Presence (PoP) in a computer network having other PoPs, said access request received from a NAS, the method including:

accessing a list of network access servers (NASes) known to the PoP and the computer network, said list located locally at the PoP; and

validating that said access request was received from a known entity by determining if an entry exists in said list for the NAS from which the access request was received.

9. The method of claim 8, further including retrieving a user record from a database of user records located locally at said PoP, said database of user records containing records for only those users who have been identified as having the PoP as their home PoP.

10. The method of claim 8, wherein each entry in said list contains a field identifying a NAS and a field identifying a dictionary of attributes supported by the corresponding NAS.

11. The method of claim 10, wherein said dictionary of attributes is a RADIUS

dictionary.

12. The method of claim 8, wherein said each entry in said list contains fields for:  
a domain name of a NAS;  
5 a vendor name of said NAS;  
a shared secret between all known NASes and AAA servers in the network; and  
a dictionary name, said dictionary name indicating a dictionary of attributes  
supported by said NAS.

13. The method of claim 12, wherein said validating further includes validating that  
said access request was received from a known entity by determining if the domain name  
that the access request was received from matches the domain name field of any entry in  
said list.

14. The method of claim 13, wherein said validating further includes examining  
whether a password supplied with said access request matches the shared secret field of a  
corresponding entry in said list if the domain name that the access request was received  
from matches the domain name field of any entry in said list.

15. The method of claim 12, wherein said dictionary of attributes is a standard  
RADIUS dictionary.

16. The method of claim 8, wherein said accessing and validating are performed by an Authentication, Authorization, and Accounting (AAA) server.

17. The method of claim 8, further including subscribing to a broker event to update

5 said list whenever a NAS known to the computer network is added, deleted, or modified.

18. A method for handling an access request at a PoP, said access request generated by a user logging on to said PoP, said user having a home PoP, the method including:

determining if said user's home PoP is said PoP;

forwarding said access request to an AAA server located at said PoP if said user's home PoP is said PoP; and

relaying said access request to said user's home PoP if said user's home PoP is not said PoP.

19. The method of claim 18, wherein said determining, forwarding, and relaying are performed by a Protocol Gateway.

20. The method of claim 18, wherein said determining includes examining a user name entered by said user.

21. The method of claim 20, wherein said determining further includes parsing said user name to reveal a PoP location indicated within said user name.

22. The method of claim 21, wherein said PoP location indicated within said user name is a city name as a prefix to said user name.

23. The method of claim 21, wherein said PoP location indicated within said user name is an abbreviation for a city name contained within a domain name affixed to the end of said user name.

24. The method of claim 20, wherein said determining further includes parsing said user name to reveal a domain name, said domain name indicating an ISP in control of said home PoP.

25. An apparatus for centrally managing a computer network including:  
a central NAS list maintainer;  
a NAS list broadcaster coupled to said central NAS list maintainer and coupled to said computer network.

26. The apparatus of claim 25, wherein said central NAS list maintainer and said NAS list broadcaster are contained within a Network Control Console.

27. The apparatus of claim 25, wherein said central NAS list maintainer is coupled to a central NAS list, said central NAS list containing entries for each NAS known to the

computer network.

28. The apparatus of claim 27, wherein each NAS known to the computer network is a NAS which has been chosen as being valid.

29. The apparatus of claim 25, wherein said NAS list broadcaster is coupled to a broker.

30. An apparatus for locally processing an access request at a PoP in a computer network having other PoPs, said access request received from a NAS, the apparatus including:

a memory configured to store a NAS list, said NAS list containing entries on each NAS known to the PoP and the computer network and located locally at the PoP;

a NAS list accessor coupled to said NAS list; and

an access request validator coupled to said NAS list accessor.

31. The apparatus of claim 30, further including:

a user record database located locally at said PoP, said user record database containing records for only those users who have been identified as having the PoP as their home PoP; and

a user record retriever coupled to said user record database and coupled to said access request validator.

32. The apparatus of claim 30, wherein each entry in said NAS list contains a field identifying a NAS and a field identifying a dictionary of attributes supported by the corresponding NAS.

5

33. The apparatus of claim 32, wherein said dictionary of attributes is a RADIUS dictionary.

34. The apparatus of claim 30, wherein said each entry in said list contains fields for:  
a domain name of a NAS;  
a vendor name of said NAS;  
a shared secret between all known NASes and AAA servers in the network; and  
a dictionary name, said dictionary name indicating a dictionary of attributes supported by said NAS.

15

35. The apparatus of claim 33, wherein said dictionary of attributes is a standard RADIUS dictionary.

36. The apparatus of claim 30, wherein said NAS list accessor and said access request validator are contained in an Authentication, Authorization, and Accounting (AAA) server.

20

37. The apparatus of claim 30, further including:  
a broker event subscriber coupled to said NAS list.

38. An apparatus for handling an access request at a PoP, said access request generated by a user logging on to said PoP, said user having a home PoP, the apparatus including:  
a user home PoP determiner; and  
an access request forwarder coupled to said user home PoP determiner, said access request forwarder coupled to an AAA server if the PoP is said user's home PoP and coupled to a computer network if the PoP is no said user's home PoP.

39. The apparatus of claim 38, wherein said user home PoP determiner and said access request forwarder are contained within a Protocol Gateway.

40. A program storage device readable by a machine, tangibly embodying a program of instructions executable by the machine to perform a method for centrally managing a computer network, the method including:  
maintaining a central database of all NASes known to the computer network; and  
broadcasting a message to a NAS list located at each POP in the computer network whenever said central database is changed, said message containing information regarding the change.

41. A program storage device readable by a machine, tangibly embodying a program



of instructions executable by the machine to perform a method for locally processing an access request at a Point-of-Presence (PoP) in a computer network having other PoPs, said access request received from a NAS, the method including:

accessing a list of network access servers (NASes) known to the PoP and the

5 computer network, said list located locally at the PoP; and

validating that said access request was received from a known entity by determining if an entry exists in said list for the NAS from which the access request was received.

42. A program storage device readable by a machine, tangibly embodying a program of instructions executable by the machine to perform a method for handling an access request at a PoP, said access request generated by a user logging on to said PoP, said user having a home PoP, the method including:

determining if said user's home PoP is said PoP;

15 forwarding said access request to an AAA server located at said PoP if said user's home PoP is said PoP; and

relaying said access request to said user's home PoP if said user's home PoP is not said PoP.

20